

LANCOM R&S® Unified Firewalls

Features: Appliances



R&S® Unified Firewalls	R&S®UF-100	R&S®UF-200	R&S®UF-300	R&S®UF-500	R&S®UF-900
Network interfaces					
Ports	4x GE copper	4x GE copper	8x GE copper	14x GE copper	8x GE copper + 2 modules
System performance					
IPS/IDS throughput (Mbps)	–	550	635	1,295	3,780
Firewall throughput (Mbps)	3,800 (UDP)	3,800 (UDP)	7,700 (UDP)	13,400 (UDP)	60,000 (UDP)
VPN throughput (Mbps)	430 (IPSec)	430 (IPSec)	620 (IPSec)	1,260 (IPSec)	4,280 (IPSec)
Concurrent sessions	1,000,000	1,000,000	1,000,000	2,000,000	16,700,000
New sessions per second	11,000	11,000	13,000	33,000	130,000
Number of users	5-30 concurrent users	5-30 concurrent users	30-100 concurrent users	100-200 concurrent users	100 concurrent users, extendable in steps of 100 to max. 500
Power					
Input voltage (V)	100-240	100-240	100-240	100-240	100-240
Power consumption (W)	36	36	150	150	2 x 300
Operating environment					
Operating temperature (°C)	0-40	0-40	0-40	0-40	0-40
Relative humidity (%)	5-90	5-90	20-90	20-90	5-90
Dimensions					
WxHxD (mm)	220 x 44 x 176	220 x 44 x 176	438 x 44 x 292	431 x 44 x 305	431 x 44 x 468