

LCOS 10.90

# LANCOM 1793VA

For professional telephony at Supervectoring connections



Efficient workflows depend on network infrastructures that offer high performance and reliability. Reason enough for you to rely on the expert for secure site connectivity and easy All-IP migration. This SD-WAN VoIP gateway supports VDSL Supervectoring with up to 300 Mbps. Designed for the combined operation of ISDN/analog and VoIP telephony components, it is the ideal device for small and medium-sized enterprises.

- Integrated VDSL Super Vectoring modem for up to 300 Mbps (backwards compatible with VDSL2 / ADSL2+)
- Continued use of existing ISDN and analog components after migrating to All-IP
- Telephony features thanks to integrated LANCOM VCM (Voice Call Manager) & SBC (session border controller)
- 2 x ISDN S0 (TE/NT + NT) for point-to-point or multipoint line configuration, 2x analog (internal) / fax
- Extension to 4x analog with LANCOM Analog Adapter Set
- SD-WAN – automatic VPN and VLAN configuration via the LANCOM Management Cloud
- 5 integrated IPSec VPN channels (25 optional)
- Network virtualization with up to 16 networks on one device (ARF)
- Security Made in Germany
- Maximum future compatibility, reliability and security



LCOS 10.90

# LANCOM 1793VA

## Support for VDSL Supervectoring

VDSL Supervectoring achieves higher data rates on existing copper lines. Speeds of up to 300 Mbps are possible. The LANCOM 1793VA offers full Supervectoring support while remaining backwards compatible with VDSL2 and ADSL2+.

## Professional telephony with the LANCOM VCM (Voice Call Manager)

The LANCOM Voice Call Manager is already integrated into the LANCOM 1793VA and provides advanced telephony support. It manages all aspects of the telephony and controls all of the PBX components connected to the router. Furthermore, it enables the easy integration of DECT telephones by autoprovisioning with the LANCOM DECT 510 IP base station.

## Integrated session border controller

The LANCOM Voice Call Manager provides the functions of a Session Border Controller: This ensures that external (unsecure) and internal (secure) networks are kept separate. Also, voice packets are given preference (Quality of Service) thanks to bandwidth reservation, which ensures a high call quality. In addition, the VCM as a SIP proxy enables the professional management of signaling and voice data for high security in the set up, implementation and teardown of telephone conversations, including any protocol conversion by means of transcoding.

## LANCOM SD-WAN – Next-level networking

With LANCOM SD-WAN you can manage and monitor your entire corporate network centrally, cost-effectively, quickly, and stress-free! In combination with the LANCOM Management Cloud, the SD-WAN gateway gives you all the options for an automated setup of secure VPN connections (Auto-VPN) between sites, including network virtualization. Highlight features such as High Scalability VPN (HSVPN) and Advanced Mesh VPN offer you a significant plus in scalability and efficiency for a large number of branches and applications. Furthermore, if multiple WAN connections are defined, they are automatically operated in active/active mode (load balancing), thereby increasing the available total bandwidth. With Dynamic Path Selection and Dynamic Traffic Steering, applications are also dynamically routed via the best connection at any given time.

## Secure communication via VPN

With virtual private networks (VPN), you use the public medium of the Internet as a communication path and secure the connection in such a way that the communication still remains completely inaccessible to external parties. This SD-WAN gateway offers you five integrated IPSec VPN channels for secure encryption, so that the protection of internal company data is always guaranteed when connecting mobile employees, home offices, or branch offices. With the LANCOM VPN Option, you can also upgrade the device to up to 25 VPN channels, so that the infrastructure can easily grow with your needs without additional hardware.



LCOS 10.90

# LANCOM 1793VA

## Layer 2 features

VLAN	4.096 IDs based on IEEE 802.1q, dynamic assignment
Multicast	IGMP-Snooping, MLD-Snooping
Protocols	Ethernet over GRE-Tunnel (EoGRE), L2TPv3, ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP, LACP
OAM	Ethernet link OAM 802.3ah, IEEE 802.1ag CFM

## Layer 3 features

Firewall	Stateful inspection firewall including packet filtering, extended port forwarding, N:N IP address mapping, packet tagging, support for DNS targets, user-defined rules and notifications
Quality of Service	Traffic shaping, bandwidth reservation, DiffServ/TOS, packet size control, layer-2-in-layer-3 tagging, support for 8 QoS queues (6 free configurable)
Security	Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button
PPP authentication mechanisms	PAP, CHAP, MS-CHAP, and MS-CHAPv2
High availability / redundancy	VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup
Router	IPv4-, IPv6-, IPv4/IPv6 dual stack
SD-WAN Application Routing	SD-WAN Application Routing in connection with the LANCOM Management Cloud
SD-WAN dynamic path selection	SD-WAN dynamic path selection in connection with the LANCOM Management Cloud
SD-WAN Zero Touch Deployment	Zero touch commissioning of the device in conjunction with the LANCOM Management Cloud
Router virtualization	ARF (Advanced Routing and Forwarding) up to separate processing of 16 contexts
IPv4 services	HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS
IPv6 services	HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS
Dynamic routing protocols	RIPv2, BGPv4, OSPFv2, LISP (Locator/ID Separation Protocol)
IPv4 protocols	DNS, HTTP, HTTPS, ICMP, NTP/SNTP, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3



# LANCOM 1793VA

## Layer 3 features

IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, BGP, LISP, Syslog, SNMPv1,v2c,v3, MLDv2, PIM, NPTv6 (NAT66), VRRPv3
Multicast Routing	PIM (Protocol Independent Multicast), IGMP proxy, MLD proxy
WAN operating mode	VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port
WAN protocols	PPPoE, Multi-PPPoE, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire and IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static)
Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd, Dual Stack Lite, 464XLAT

## Security

Intrusion Prevention	Monitoring and blocking of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
URL blocker	Filtering of unwanted URLs based on DNS hitlists and wildcard filters. Extended functionality with Content Filter Option
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP traps and SYSLOG
Authentication mechanisms	PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanism
Anti-theft	Anti-theft ISDN site verification over B or D channel (self-initiated call back and blocking)
Adjustable reset button	Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot'

## High availability / redundancy

VRRP	VRRP (Virtual Router Redundancy Protocol VRRPv2 and VRRPv3) for backup in case of failure of a device or remote station.
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
ISDN backup	In case of failure of the main connection, a backup connection is established over ISDN. Automatic return to the main connection
Analog/GSM modem backup	Optional operation of an analog or GSM modem at the serial interface



# LANCOM 1793VA

## High availability / redundancy

Load balancing	Static and dynamic load balancing over up to 4 WAN connections (incl. client binding).
VPN redundancy	Backup of VPN connections across different hierarchy levels, e.g. in case of failure of a central VPN concentrator and re-routing to multiple distributed remote sites. Any number of VPN remote sites can be defined (the tunnel limit applies only to active connections). Up to 32 alternative remote stations, each with its own routing tag, can be defined per VPN connection. Automatic selection may be sequential, or dependant on the last connection, or random (VPN load balancing)
Line monitoring	Line monitoring with LCP echo monitoring, dead-peer detection and up to 4 addresses for end-to-end monitoring with ICMP polling

## VPN

IPSec over HTTPS	Enables IPSec VPN based on TCP (at port 443 like HTTPS) which can go through firewalls in networks where e. g. port 500 for IKE is blocked. Suitable for client-to-site connections and site-to-site connections. IPSec over HTTPS is based on the NCP VPN Path Finder technology
Number of VPN tunnels	Max. number of concurrent active IPSec, PPTP (MPPE) and L2TPv2 tunnels: 5 (25 with VPN 25 Option). Unlimited configurable connections. Configuration of all remote sites via one configuration entry when using the RAS user template or Proadaptive VPN.
Hardware accelerator	Integrated hardware accelerator for 3DES/AES encryption and decryption
Realtime clock	Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case
Random number generator	Generates real random numbers in hardware, e. g. for improved key generation for certificates immediately after switching-on
1-Click-VPN Client assistant	One click function in LANconfig to create VPN client connections, incl. automatic profile creation for the LANCOM Advanced VPN Client
1-Click-VPN Site-to-Site	Creation of VPN connections between LANCOM routers via drag and drop in LANconfig
IKE, IKEv2	IPSec key exchange with Preshared Key or certificate (RSA signature, ECDSA-Signature, digital signature)
Smart Certificate*	Convenient generation of digital X.509 certificates via an own certification authority (SCEP-CA) on the webpage or via SCEP.
Certificates	X.509 digital multi-level certificate support, compatible with Microsoft Server / Enterprise Server and OpenSSL. Secure Key Storage protects a private key (PKCS#12) from theft.
Certificate rollout	Automatic creation, rollout and renewal of certificates via SCEP (Simple Certificate Enrollment Protocol) per certificate hierarchy
Certificate revocation lists (CRL)	CRL retrieval via HTTP per certificate hierarchy
OCSP Client	Check X.509 certifications by using OCSP (Online Certificate Status Protocol) in real time as an alternative to CRLs
OCSP Server/Responder*	Offers validity information for certificates created with Smart Certificate via OCSP



# LANCOM 1793VA

## VPN

<b>XAUTH</b>	XAUTH client for registering LANCOM routers and access points at XAUTH servers incl. IKE-config mode. XAUTH server enables clients to register via XAUTH at LANCOM routers. Connection of the XAUTH server to RADIUS servers provides the central authentication of VPN-access with user name and password. Authentication of VPN-client access via XAUTH and RADIUS connection additionally by OTP token
<b>RAS user template</b>	Configuration of all VPN client connections in IKE ConfigMode via a single configuration entry
<b>Proadaptive VPN</b>	Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections.
<b>Algorithms</b>	3DES (168 bit), AES-CBC and -GCM (128, 192 or 256 bit), RSA (1024-4096 bit), ECDSA (P-256-, P-384-, P-521-curves) and Chacha20-Poly 1305. OpenSSL implementation with FIPS-140 certified algorithms. MD-5, SHA-1, SHA-256, SHA-384 or SHA-512 hashes
<b>NAT-Traversal</b>	NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough
<b>LANCOM Dynamic VPN</b>	Enables VPN connections from or to dynamic IP addresses. The IP address is communicated via ISDN B- or D-channel or with the ICMP or UDP protocol in encrypted form. Dynamic dial-in for remote sites via connection template
<b>MOBIKE</b>	IKEv2 VPN clients can seamlessly switch between different networks (e.g. from WLAN to mobile radio) without having to re-establish the VPN tunnel
<b>Dynamic DNS</b>	Enables the registration of IP addresses with a Dynamic DNS provider in the case that fixed IP addresses are not used for the VPN connection
<b>Specific DNS forwarding</b>	DNS forwarding according to DNS domain, e.g. internal names are translated by proprietary DNS servers in the VPN. External names are translated by Internet DNS servers
<b>Split DNS</b>	Allows the selective forwarding of traffic for IKEv2 depending on the addressed DNS domain.
<b>IPv4 VPN</b>	Connecting private IPv4 networks
<b>IPv4 VPN over IPv6 WAN</b>	Use of IPv4 VPN over IPv6 WAN connections
<b>IPv6 VPN</b>	Connecting private IPv6 networks
<b>IPv6 VPN over IPv4 WAN</b>	Use of IPv6 VPN over IPv4 WAN connections
<b>Radius</b>	RADIUS authorization and accounting, outsourcing of VPN configurations in external RADIUS server in IKEv2, RADIUS CoA (Change of Authorization)
<b>High Scalability VPN (HSVPN)</b>	Transmission of multiple, securely separated networks within a VPN tunnel
<b>Advanced Mesh VPN</b>	On demand dynamic VPN tunnel establishment between branches
<b>IKEv2-EAP*</b>	VPN clients can be authenticated with IKEv2-EAP against a central database like Microsoft Windows Server or RADIUS Server
<b>Two-factor authentication*</b>	Two-factor authentication with LANCOM Advanced VPN Client via IKEv2 EAP-OTP
<b>*)</b>	Only with VPN 25 option



LCOS 10.90

# LANCOM 1793VA

## Performance

Routing-Performance	Data regarding the overall routing performance can be found inside the LANCOM tech paper "Routing-Performance" on <a href="http://www.lancom-systems.com">www.lancom-systems.com</a>
---------------------	--

## VoIP

Number of local subscribers	10 (up to 40 with VoIP +10 Option)
Number of local ISDN subscribers	Up to 2 internal ISDN buses each with 2 parallel channels and each up to 10 telephone numbers
Number of simultaneous VoIP connections	Up to 60 external VoIP connections depending on code conversion, echo canceling and load
Functionality	Hold/Request, Swap, Transfer, Call Forwarding (CFU, CFB, CFNR), number display/suppression (CLIP, CLIR), suppression of second call (Busy on Busy), immediate outgoing line, hunt groups, call diversion, overlap dialing
Hunt groups	Hunt group cascades, Call diversion, simultaneously or sequentially. Automatic forwarding after timeout or when busy/unreachable
Call router	Central switching of all incoming and outgoing calls. Number translation by mapping, numeral replacement and number supplementation. Configuration of line and route selection incl. line backup. Routing based on calling and called number, SIP domain and line. Blocking of telephone numbers or blocks of telephone numbers. Inclusion of local subscribers into the number range of an upstream PBX. Supplement/remove line-related prefixes or switchboard numbers.
SIP proxy	Up to 25 SIP-provider accounts (up to 55 with VoIP +10 Option), up to 4 SIP PBXs incl. line backup. SIP connections from/to internal subscribers, SIP providers and SIP PBXs. Automatic bandwidth management and automatic configuration of the firewall for SIP connections.
SIP gateway	Conversion of analog or ISDN telephone calls to SIP calls, and vice versa. Local ISDN and analog subscribers register as local SIP users, and local ISDN/analog subscribers automatically register as SIP users at upstream SIP PBXs or SIP providers. Number translation between internal numbers and MSN/DDI
SIP trunk	Call switching based on extension numbers to/from VoIP PBXs/VoIP providers (support of the VoIP-DDI functions compliant with ITU-T Q.1912.5). Mapping of entire VoIP telephone number blocks
Session Border Controller (SBC)	Separation of insecure and secure networks, QoS, management of signaling and voice data, transcoding
Media protocols	RTP, SIPs and SRTP
ISDN features	Operation at ISDN exchange line or at ISDN extension line of existing PBXs. Provision of exchange lines or extension lines
Analog features	Internal FXS ports for one analog terminal device each, or as an analog PBX exchange line.
SIP-Codec support	SIP only: G.711 $\mu$ -law/A-law (64 kbps), G.722, G.723, G.726, G.729, iLBC, PCM (16, 20 und 24 Bit, Mono und Stereo), OPUS, AAC (LC, HE HEV2), MPEG Layer II, ADPCM 4SB. DTMF support (Inband, RFC2833, SIP-INFO)
Fax transmission	Transmission of fax via SIP on the LAN/WAN side with T.38 or G.711. Conversion of SIP fax with T.38 and break-in/break-out at the outside line to ISDN G.711 with service signalisation. Connection and conversion to SIP T.38 or G.711 for SIP, analog or ISDN fax machines. Compatible to SwyxFax on true G.711 SIP lines.



# LANCOM 1793VA

## VoIP

Autoprovisioning	Automatic network and VoIP integration of LANCOM DECT 510 IP base station
SIP ALG	The SIP ALG (Application Layer Gateway) acts as a proxy for SIP communication. For SIP calls the ALG opens the necessary ports for the corresponding media packets. Automatic address translation (STUN is no longer needed).

## Interfaces

WAN: VDSL / ADSL2+	→ VDSL2 compliant with ITU G.993.2, profiles 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a, 35b → VDSL Supervectoring as per ITU G.993.2 (Annex Q) → VDSL2 Vectoring: as per ITU G.993.5 (G.Vector) → ADSL2+ over ISDN as per ITU G.992.5 Annex B/J with DPBO, ITU G.992.3/5 and ITU G.992.1 → ADSL2+ over POTS as per ITU G.992.5 Annex A/M with DPBO, ITU G.992.3 and ITU G.992.1 → Supports one virtual ATM circuit (VPI, VCI pair) at a time
Ethernet ports	4 individual 10/100/1000 Mbps Ethernet ports; up to 3 ports can be operated as additional WAN ports with load balancing. Ethernet ports can be electrically disabled within LCOS configuration. The ports support energy saving according to IEEE 802.3az
Port configuration	Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). LAN ports can be operated as a switch or separately. Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing. DMZ ports can be operated with their own IP address range without NAT
USB 2.0 host port	USB 2.0 hi-speed host port for connecting USB printers (USB print server), serial devices (COM port server), USB data storage (FAT file system); bi-directional data exchange is possible
ISDN	1x ISDN BRI port (NT) and 1x internal/external ISDN port (NT/TE)
Analog	4x internal FXS ports (Analog1, Analog2, Analog3, Analog4) each for one analog device
Serial interface	Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud, suitable for optional connection of analog/GPRS modems. Supports internal COM port server and allows for transparent asynchronous transmission of serial data via TCP

## Management and monitoring

Management	LANCOM Management Cloud, LANconfig, WEBconfig, LANCOM Layer 2 management (emergency management)
Management functions	Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job
FirmSafe	Two stored firmware versions, incl. test mode for firmware updates
automatic firmware update	configurable automatic checking and installation of firmware updates
Monitoring	LANCOM Management Cloud, LANmonitor, WLANmonitor
Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events





LCOS 10.90

# LANCOM 1793VA

## Management and monitoring

Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG, Layer 7 Application Detection including application-centric tracking of traffic volume
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
Netflow	Export of information about incoming and outgoing IP traffic
SD-LAN	SD-LAN – automatic LAN configuration via the LANCOM Management Cloud
SD-WAN	SD-WAN – automatic WAN configuration via the LANCOM Management Cloud

## Hardware

Weight	1,1 lbs (500 g)
Environment	Temperature range 0–35° C; humidity 0–95%; non-condensing
Housing	Robust synthetic housing, rear connectors, ready for wall mounting, Kensington lock; 210 x 45 x 140 mm (W x H x D)
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	15 watt

## Declarations of conformity\*

Europe/EFTA	CE
Country of Origin	Made in Germany
* ) Note	You will find all declarations of conformity on our website at <a href="http://www.lancom-systems.com/doc">www.lancom-systems.com/doc</a>

## Scope of delivery

Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
Cable	DSL cable for IP based communications incl. galvanic signature, 4,25m
Adapter	2x TAE adapter (RJ11 to TAE)
Power supply unit	External power adapter (230 V), NEST 12 V/2.0 A DC/S, coaxial power connector 2.1/5.5 mm, temperature range from -5 to +45° C, LANCOM item no. 111303 (EU)

## Support

Warranty extension	Free warranty extension up to 3 years (replacement service for defects) For details, please refer to the service and support conditions at <a href="http://www.lancom-systems.com/support-conditions">www.lancom-systems.com/support-conditions</a> or at <a href="http://www.lancom.de/rma">www.lancom.de/rma</a> .
--------------------	---



# LANCOM 1793VA

## Support

Security updates	Up to 2 years after End of Sale of the device (but min. 3 years, see <a href="http://www.lancom-systems.com/product-tables">www.lancom-systems.com/product-tables</a> ), can be extended by purchasing LANcare products
Software updates	Regular free updates including new features as part of the LANCOM Lifecycle Management ( <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a> )
Manufacturer support	For LANcommunity partners up to the End of Life of the device For end customers with LANcare Direct or LANcare Premium Support during the LANcare validity
LANcare Basic S	Security updates until EOL (min. 5 years) and 5 years replacement service with shipment of the replacement device within 5 days after arrival of the defective device (8/5/5Days), item no. 10720
LANcare Advanced S	Security updates until EOL (min. 5 years) and 5 years NBD advance replacement with delivery of the replacement device within one business day (8/5/NBD), item no. 10730
LANcare Direct Advanced 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10776, 10777 or 10778)
LANcare Direct 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10752, 10753 or 10754)
LANcare Direct Advanced 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10764, 10765 or 10766)
LANcare Direct 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10740, 10741 or 10742)

## Software

Lifecycle Management	After discontinuation (End of Sale), the device is subject to the LANCOM Lifecycle Management. Details can be found at: <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a>
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security.

## Options

VPN	LANCOM VPN-25 Option (25 channels), item no. 60083
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 100), 1 year subscription, item no. 61590
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 100), 1 year subscription, item no. 61591



LCOS 10.90

# LANCOM 1793VA

## Options

LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 100), 1 year subscription, item no. 61592
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 100), 3 year subscription, item no. 61593
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 100), 3 year subscription, item no. 61594
LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 100), 3 year subscription, item no. 61595
LANCOM BPjM Filter	LANCOM BPjM Filter Option, 5 years subscription, item no. 61418
LANCOM Public Spot	Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network, item no. 60642
LANCOM Public Spot (10 bulk)	Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network (10 bulk), item no. 61312
LANCOM Public Spot PMS Accounting Plus	Extension of the LANCOM Public Spot (XL) Option for the connection to hotel billing systems with FIAS interface (such as Micros Fidelio) for authentication and billing of guest accesses for 178x/19xx routers, 2100EF, WLCs, and current central-site gateways, item no. 61638
LANCOM WLC Basic Option for Routers	LANCOM WLC Basic Option for Routers for up to 6 managed LANCOM access points or WLAN routers, item no. 61639
LANCOM WLC AP Upgrade +6	LANCOM WLC AP Upgrade +6 Option, enables your WLC to manage 6 Access Points/WLAN router in addition, item no. 61629
LANCOM VoIP +10 Option	Upgrade for LANCOM VoIP router with 10 additional internal VoIP numbers (additionally up to 40) and 10 external SIP lines (additionally up to 55) item no. 61423

## LANCOM Management Cloud

LANCOM LMC-B-1Y LMC License	LANCOM LMC-B-1Y License (1 Year), enables the management of one category B device for one year via the LANCOM Management Cloud, item no. 50103
LANCOM LMC-B-3Y LMC License	LANCOM LMC-B-3Y License (3 Years), enables the management of one category B device for three years via the LANCOM Management Cloud, item no. 50104
LANCOM LMC-B-5Y LMC License	LANCOM LMC-B-5Y License (5 Years), enables the management of one category B device for five years via the LANCOM Management Cloud, item no. 50105

## Accessories

LANCOM DECT 510 IP (EU)	Professional DECT base station for up to 6 DECT phones, network integration and configuration via LANCOM VoIP router, 4 simultaneous calls possible, highest voice quality, power supply via PoE or power supply unit, item no. 61901
19" Rack Mount	19" rack mount adaptor, item no. 61501
LANCOM Wall Mount	For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61349



LCOS 10.90


# LANCOM 1793VA

## Accessories

LANCOM Wall Mount (White)	For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61345
LANCOM Serial Adapter Kit	For the connection of V.24 modems with AT command set and serial interface for the connection to the LANCOM COM interface, incl. serial cable and connection plug, item no. 61500
LANCOM Analog Adapter Set	For connection of 2 further analogue terminals, item no. 62599
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - single license, item no. 61600
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 10 licenses, item no. 61601
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 25 licenses, item no. 61602
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), single license, item no. 61606
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), 10 licenses, item no. 61607

## Item number(s)

LANCOM 1793VA (EU)	62114
--------------------	-------



LANCOM Systems GmbH  
A Rohde & Schwarz Company  
Adenauerstr. 20/B2  
52146 Wuerselen | Germany  
info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 02/25