

LANCOM GS-1108P

Unmanaged 8-port Gigabit Ethernet switch with Power over Ethernet for reliable networks



The LANCOM GS-1108P is ideal for operation in smaller offices, business premises, and home offices. It provides reliable networking of up to 8 network components and, with a switching capacity of up to 16 Gbps, it handles large data volumes with ease. By supporting Power over Ethernet IEEE 802.3af/at on all ports, the switch is an efficient way of supplying power to PoE-enabled network components—no separate power cabling is required. The switch has an integrated power supply adapter and, with its robust non-slip metal housing, it is highly resistant to everyday knocks. The package includes an adapter for 19"-cabinet mounting.

- Compact 8-port Gigabit Ethernet switch for reliable networking of small offices and the efficient power supply of PoE-enabled network components
- PoE support as per IEEE 802.3af/at with 60 W power consumption for efficient and centralized power supply
- Integrated power supply unit and quiet fan
- Robust, shock-resistant metal housing with maximum slip-resistance
- Adapters for 19" cabinet mounting included



LANCOM GS-1108P

High power output on 8 ports

The LANCOM GS-1108P is equipped with 8 Gigabit Ethernet ports. With a data throughput of 16 Gbps on the backplane, it offers full performance even under load. This switch is a high-performance basis for modern network infrastructures in small and home offices.

Centralized power supply without additional cabling

The LANCOM GS-1108P is a high-performance PoE switch that directly powers PoE devices connected to it; there is no need of additional power supply units or cabling. It supports the two Power-over-Ethernet standards, IEEE 802.3af and IEEE 802.3at (PoE+). It has high power-output reserves and an overall output of 60 Watts makes it an efficient power supply for PoE devices.

Space-saving and quiet

The integrated power supply makes the LANCOM GS-1108 a real space saver that finds its place even in the smallest offices. Its integrated fan is extremely quiet, making the switch an ideal desktop switch for small installations.

Robust metal housing

The robust and non-slip metal housing is effective protection for the desktop switch against outside influences as it is highly resistant to everyday knocks. The supplied adapter additionally allows the device to be mounted in a standard 19" cabinet.



LANCOM GS-1108P

Operating modes

Switching	Store and forward
Auto MDI/MDI-X	Yes
Transfer mode	10/100/1000 mbit/s, full/half-duplex (auto sensing)
Flow control	IEEE 802.3x flow control in full duplex mode
Display	LEDs: power, link/act, speed, PoE activity
Throughput	16 GBit/s

PoE with IEEE 802.3at

Ports	8x IEEE 802.3at PoE ports (compatible to IEEE 802.3af powered devices), limited by the maximum PoE power supplied
-------	---

Hardware

Weight	2,20 lbs (1 kg)
Power supply	Internal power supply unit (100 – 240 V, 50 – 60 Hz)
Environment	Temperature range 0 – 40° C; humidity 10 – 90%; non-condensing
Housing	Robust metal housing, 19" 1U (220 x 44 x 135 mm > W x H x D) with removable mounting brackets, network connectors on the front
Fans	1 silent fan
Power consumption (max)	70 W (PoE power budget = 60 W)

Declarations of conformity*

Europe/EFTA	CE
North America	FCC/IC
Australia / New Zealand	ACMA
*) Note	The full text of the specific Declaration of Conformity is available at the following Internet address: www.lancom-systems.com/doc

Supported IEEE standards

IEEE 802.3	10Base-T Ethernet
IEEE 802.3ab	1000Base-TX Ethernet
IEEE 802.3af	Power over Ethernet (PoE)



LANCOM GS-1108P

Supported IEEE standards

IEEE 802.3at	Power over Ethernet Plus (PoE+)
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.3u	100Base-T Ethernet
IEEE 802.3x	Flow Control

Scope of delivery


Manual	Printed Installation Guide (DE/EN)
Cable	IEC power cord
19" brackets	Two 19" brackets for rackmounting

Support

Warranty extension	2 years (replacement service for defects), For details, please refer to the service and support conditions at www.lancom-systems.com/support-conditions or at www.lancom.com/rma
Manufacturer support	→ For LANcommunity partners up to the End of Life of the device → For end customers with LANcare Premium Support during the LANcare validity

Item number(s)

LANCOM GS-1108P	61430
-----------------	-------



LANCOM Systems GmbH
 A Rohde & Schwarz Company
 Adenauerstr. 20/B2
 52146 Wuerselen | Germany
info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 08/24