

LANCOM GS-2310P+

Managed 10-port Gigabit Ethernet switch with Power over Ethernet for reliable networks



The LANCOM GS-2310P+ is a reliable component for smaller modern network infrastructures at small or home offices. It networks up to 10 devices with its 8 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). This switch supplies an overall output of 130 Watts and is also capable of powering all PoE devices connected to it (as per IEEE 802.3af/at) without any additional power supply units or cabling. Equipped with numerous security features and a high-performance hardware platform, it is ideal for the secure and reliable networking of smaller networks.

- 8 Gigabit Ethernet and 2 combo ports (TP/SFP)
- PoE support based on IEEE 802.3af/at with 130 W input power for an efficient and central power supply
- Energy-saving functions as per IEEE 802.3az with port deactivation if no data is transferred
- Fanless Design
- Security with configurable access control on all ports as per IEEE 802.1X
- Secure remote management through TACACS+, SSH, SSL, and SNMPv3
- Zero-touch deployment
- IPv6 and IPv4 support for modern enterprise networks
- 5-year warranty on all components



LANCOM GS-2310P+

High power output on 10 ports

The LANCOM GS-2310P+ is equipped with 8 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). With a data throughput of 20 Gbps on the backplane, it offers full performance even under load. This makes the switch a high-performance basis for modern network infrastructures in small and home offices.

Centralized power supply without additional cabling

The LANCOM GS-2310P+ is a high-performance PoE switch that directly powers PoE devices connected to it; there is no need of additional power supply units or cabling. It supports the two Power-over-Ethernet standards, IEEE 802.3af and IEEE 802.3at (PoE+). It has plenty in reserve with an overall output of 130 Watts, so it efficiently supplies power to devices with high energy demands.

Efficient power-saving features

Featuring Energy Efficient Ethernet technology, the LANCOM GS-2310P+ provides optimum energy efficiency even at fast data rates. Thanks to numerous power-saving features based on the IEEE 802.3az standard, ports that are not transferring data are switched off automatically. This valuable feature saves precious resources.

Configurable access control

The LANCOM GS-2310P+ excludes rogue clients from gaining unauthorized access to the network. This is ensured by secured access control on all ports as per IEEE 802.1X (port-based, single, multi, and MAC-based).

Secure remote management

Secure communication protocols such as SSH, SSL, and SNMPv3 mean that the LANCOM GS-2310P+ is ideal for professional remote network management. The switch also supports the TACACS+ protocol for authentication, authorization, and accounting. This optimized solution promises maximum security for multi-site network management and monitoring.

Zero-touch deployment

Quick and easy network integration of the switch as well as automatic assignment of the configuration—without manual configuration. For installations based on the LANCOM Management Cloud, switch receives the correct configuration immediately after network authentication.

IPv6 and IPv4 support

Thanks to the dual-stack implementation, the LANCOM GS-2310P+ operates in pure IPv4, pure IPv6, or in mixed networks. Applications such as SSL, SSH, Telnet, and TFTP can continue to be operated on IPv6 networks. Supported IPv6 features include stateless auto-configuration, the discovery of neighboring devices, and MLD snooping.



LANCOM GS-2310P+

Security

Secure Shell Protocol (SSH)	SSH for a secure remote configuration
Secure Sockets Layer (SSL)	SSL to encrypt HTTP connections; advanced security for browser-based configuration via web interface
IEEE 802.1X	IEEE 802.1X access control on all ports; RADIUS for authentication, authorization and accounting with e.g. MD5 hashing; guest VLAN; dynamic VLAN assignment
Private VLAN edge	Layer 2 isolation between clients in the same VLAN ("protected ports"); support multiple uplinks
Port security	Locking of MAC addresses to ports; limiting of the number of learned MAC addresses
IP source guard	Blocking access for illegal IP addresses on specific ports
Access control lists	Drop or rate limitation of connections based on source and destination MAC addresses, VLAN ID, IP address (IPv4/IPv6), protocol, port, DSCP/IP precedence, TCP/UDP source and destination ports, IEEE 802.1p priority, ICMP packets, IGMP packets, TCP flag
RADIUS/TACACS+	Authentication, authorization and accounting of configuration changes by RADIUS or TACACS+
Storm Control	Multicast/Broadcast/Unicast storm suppression
Isolated Group	Allows certain ports to be designated as protected. All other ports are non-isolated. Traffic between isolated group members is blocked. Traffic can only be sent from isolated group to non-isolated group.

Performance

Switching technology	Store and forward with latency less than 4 microseconds
MAC addresses	Support of max 8K MAC addresses
Throughput	Max. 20 Gbps on the backplane
Maximum packet processing	14,88 million packets per second (mpps) at 64-byte packets
Single IP Management (SIP)	Supports stacking of up to 16 devices, several switches can be managed via one ip address
VLAN	Port based and IEEE 802.1q tag based VLAN with up to 4,093 VLAN; Supports ingress and egress packet filter in port based VLAN
Jumbo frame support	Jumbo frame support with up to 9k frames

PoE with IEEE 802.3at

Ports	8x IEEE 802.3at PoE ports (compatible to IEEE 802.3af powered devices), limited by the maximum PoE power supplied
Power	130 W total power with dynamic load balancing on all ports



LANCOM GS-2310P+

Energy efficiency (Green Ethernet)

Energy detection Energy efficiency according to IEEE 802.3az. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up

Cable length detection Adjusts the signal strength based on the cable length. Reduces the power consumption for short cable

Layer 2 switching

Spanning Tree Protokoll (STP) / Rapid STP / Multiple STP Standard Spanning Tree according to IEEE 802.1d with fast convergence support of IEEE 802.1w (RSTP); using Multiple Spanning Tree instances by default according to IEEE 802.1s (MSTP)

Link Aggregation Control Protocol (LACP) Support of 5 groups containing up to 2 ports each according to IEEE 802.3ad

VLAN Support for up to 4K VLANs simultaneously (out of 4096 VLAN Ids); matching due to port, IEEE 802.1q tagged VLANs or MAC addresses

Voice VLAN Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS

IGMP multicasts IGMP v1, v2, v3 to limit bandwidth-intensive multicast traffic to ports with requesters; supports 256 multicast groups; source-specific multicasting

IGMP querier Support of multicast domains of snooping switches in the absence of a multicast router

IGMP proxy IGMP proxy to pass IGMP messages through

Generic VLAN registration VLAN registration with GVRP according to IEEE 802.1q for automatic delivery of VLANs in bridged domains

DHCP Relay Agent Relay of DHCP broadcast request to different LANs

Supported DHCP options
 → DHCP option 66
 → DHCP option 67
 → DHCP option 82

Interfaces

Ethernet
 → 8 TP ports 10/100/1000 Mbps
 → 2 combo ports (TP/SFP) with 100/1000 Mbps (SFP) and 10/100/1000 Mbps (TP)
 → 10 concurrent Ethernet ports in total

Console port RJ45 configuration port for command line access

Management and monitoring

Management LANconfig, WEBconfig, LANCOM Management Cloud, Industry Standard CLI

Command Line Interface (CLI) Configuration and status display from the command line with console application and direct connection to console port, via Telnet or SSH



LANCOM GS-2310P+

Management and monitoring

Monitoring	LANmonitor, LANCOM Management Cloud
Remote Monitoring	Integrated RMON software agent supports 4 RMON groups (history, statistics, alarms and events) for enhanced traffic management, monitoring and analysis
Easy-Configuration-Ports	Easy setup of ports for QoS and Security based on pre-defined configuration profiles
Port Mirroring	Traffic can be mirrored from on port to another for investigation with network analyzer or RMON probe. Up to 9 ports can be mirrored to a single mirror port. Single sessions can be selected
Security	Access rights (read/write) can be set up separately, access control list
SNMP	SNMP management via SNMPv1, v2c or v3 with support of traps. User-based security model for SNMPv3 (USM)
Diagnosis	Diagnosis from the switch with PING and cable diagnosis
Firmware update	<ul style="list-style-type: none"> → Update via WEBconfig and browser (HTTP/HTTPS) → Update via TFTP and LANconfig → Dual firmware image to update during operation
Secure Copy	Securely import and export files
DHCP client	Automatic assignement of the management IP address by DHCP
SNTP	Automatic time settings with Simple Network Time Protocol (SNTP)
s-flow	Standard for monitoring of high-speed-networks. Visualization of network use, accounting an analsation to protect your network against dangers

Hardware

Weight	5,18 lbs (2,35 kg)
Power supply	Internal power supply unit (100 – 240 V, 50 – 60 Hz)
Environment	Temperature range 0 – 40° C; humidity 10 – 90%; non-condensing
Housing	Robust metal housing (220 x 45 x 242 mm > W x H x D) with mounting brackets for 19-inch mounting, network connectors on the front
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	160 W

Declarations of conformity*

Europe/EFTA	CE
North America	FCC/IC



LANCOM GS-2310P+

Declarations of conformity*

Australia / New Zealand	ACMA
Japan	VCCI
Singapore	IMDA
*) Note	
The full text of the specific Declaration of Conformity is available at the following Internet address: www.lancom-systems.com/doc	

Supported IEEE standards

IEEE 802.1AB	Link Layer Discovery Protocol (LLDP)
IEEE 802.1AB	LLDP-MED
IEEE 802.1ad	Q-in-Q tagging
IEEE 802.1d	MAC Bridging
IEEE 802.1d	Spanning Tree
IEEE 802.1p	Class of Service
IEEE 802.1q	VLAN
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1X	Port Based Network Access Control
IEEE 802.3	10Base-T Ethernet
IEEE 802.3ab	1000Base-TX Ethernet
IEEE 802.1ax, incl. 802.3ad	Link Aggregation Control Protocol (LACP)
IEEE 802.3af	Power over Ethernet (PoE)
IEEE 802.3at	Power over Ethernet Plus (PoE+)
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.3u	100Base-T Ethernet
IEEE 802.3x	Flow Control
IEEE 802.3z	1000Base-X Ethernet



LANCOM GS-2310P+

Supported RFC standards

RFC 854	Telnet Protocol Specification
RFC 1213	MIB II
RFC 1215	SNMP Generic Traps
RFC 1493	Bridge MIB
RFC 1769	Simple Network Time Protocol (SNTP)
RFC 2021	Remote Network Monitoring MIB v2 (RMONv2)
RFC 2233	Interface MIB
RFC 2613	SMON MIB
RFC 2617	HTTP Authentication
RFC 2665	Ethernet-Like MIB
RFC 2674	IEEE 802.1p and IEEE 802.1q Bridge MIB
RFC 2818	Hypertext Transfer Protocol Secure (HTTPS)
RFC 2819	Remote Network Monitoring MIB (RMON)
RFC 2863	Interface Group MIB using SMIv2
RFC 2933	IGMP MIB
RFC 3019	MLDv1 MIB
RFC 3414	User based Security Model for SNMPv3
RFC 3415	View based Access Control Model for SNMP
RFC 3635	Ethernet-Like MIB
RFC 3636	IEEE 802.3 MAU MIB
RFC 4133	Entity MIBv3
RFC 4188	Bridge MIB
RFC 4251	The Secure Shell Protocol Architecture (SSH)
RFC 4668	RADIUS Authentication Client MIB
RFC 4670	RADIUS Accounting MIB



LANCOM GS-2310P+

Supported RFC standards

RFC 5519	Multicast Group Membership Discovery MIB
RFC 7513	DHCP Snooping

Scope of delivery

Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
Cable	Serial configuration cable, 1.5m
Cable	IEC power cord
19" brackets	Two 19" brackets for rackmounting

Support

Warranty	5 years, for details, please refer to the General Warranty Conditions at: www.lancom-systems.com/warranty-conditions
Manufacturer support	Technical manufacturer support as part of a support contract (LANcommunity partner, LANcare Direct, or LANcare Premium Support)
LANcare Advanced S	Security updates and manufacturer support until EOL status (min. 5 years, support contract required: LANcommunity partner, LANcare Direct, or LANcare Premium Support), 5 years NBD advance replacement with delivery of the device on the next business day (8/5/NBD), item no. 10730
LANcare Direct Advanced 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10776, 10777 or 10778)
LANcare Direct 24/7 S	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10752, 10753 or 10754)
LANcare Direct Advanced 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10764, 10765 or 10766)
LANcare Direct 10/5 S	Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10740, 10741 or 10742)

LANCOM Management Cloud

LANCOM LMC-A-1Y LMC License	LANCOM LMC-A-1Y License (1 Year), enables the management of one category A device for one year via the LANCOM Management Cloud, item no. 50100
-----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------



LANCOM GS-2310P+

LANCOM Management Cloud

LANCOM LMC-A-3Y LMC License LANCOM LMC-A-3Y License (3 Years), enables the management of one category A device for three years via the LANCOM Management Cloud, item no. 50101

LANCOM LMC-A-5Y LMC License LANCOM LMC-A-5Y License (5 Years), enables the management of one category A device for five years via the LANCOM Management Cloud, item no. 50102

Accessories*

1000Base-SX SFP module LANCOM SFP-SX-LC1, item no. 61556

1000Base-SX SFP module LANCOM SFP-SX2-LC1, item no. 60183

1000Base-LX SFP module LANCOM SFP-LX-LC1, item no. 61557

1000Base-LX SFP BiDi module LANCOM SFP-BiDi1550-SC1, item no. 60201

LANCOM Power Cord (UK) IEC power cord, UK plug, item no. 61650

LANCOM Power Cord (CH) IEC power cord, CH plug, item no. 61652


LANCOM Power Cord (US) IEC power cord, US plug, item no. 61651

LANCOM Power Cord (AU) IEC power cord, AU plug, item no. 61653

*) Note Support for third-party accessories (SFP and DAC) is excluded and cannot be granted

Item number(s)

LANCOM GS-2310P+ 61440



LANCOM Systems GmbH
A Rohde & Schwarz Company
Adenauerstr. 20/B2
52146 Wuerselen | Germany
info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 02/24