

## LANCOM SPSU-400

Hot-swappable power supply units for LANCOM YS-7154CF (F2B / B2F)



The reliability of the LANCOM YS-7154CF plays a key role in ensuring maximum network availability and operational stability. For continuous power supply to the aggregation switch, the 400 watts power supply units LANCOM SPSU-400-B2F or SPSU-400-F2B can be used. These units are tailored to the airflow design of the switch model – whether front-to-back (F2B) or back-to-front (B2F). The hot-swappable power supplies can be easily replaced during operation, providing uninterrupted network availability.

- 400 watts power supply unit for improved failover of the LANCOM YS-7154CF (F2B / B2F)
- Hot-swappable - can be applied during operation
- Input voltage: 100 VAC und 240 VAC
- Output voltage: +12 V @37,5 A, +5 Vsb @3 A
- Over current protection
- Over voltage protection
- Short circuit protection
- Operating temperature: 0°C to 40°C
- LANCOM SPSU-400-F2B for LANCOM YS-7154CF-F2B
- LANCOM SPSU-400-F2B for LANCOM YS-7154CF-F2B



# LANCOM SPSU-400

## Technical Information

Input voltage	100 - 240 VAC, 50 - 60 Hz
---------------	---------------------------

Output power	400 W
--------------	-------

## Mechanical Information

Dimensions	211 mm (L) x 40 mm (H) x 50.5 mm (W)
------------	--------------------------------------

Weight	1200 g
--------	--------

Operating temperature	0° to 40°C
-----------------------	------------

Storage temperature	-40° to 70°C
---------------------	--------------

## Support

Warranty extension	2 years
--------------------	---------

## Further informations

Supported devices	→ LANCOM YS-7154CF-F2B, article number: #61907 → LANCOM YS-7154CF-B2F, article number: #61908
-------------------	--

## Item number(s)

SPSU-400-F2B	61922
--------------	-------

SPSU-400-B2F	61923
--------------	-------