

LANCOM SPSU-750

Hot-swappable power supply units for uninterrupted operation of LANCOM CS-8132F (F2B / B2F)



The reliability of the LANCOM CS-8132F is essential for ensuring maximum availability and operational stability across the entire network. To provide a continuous power supply to the core switch, two different 750 watts power supply units LANCOM SPSU-750-B2F and SPSU-750-F2B are available, each tailored to the airflow design of the switch variants (front-to-back (F2B) or back-to-front (B2F)). These hot-swappable power supply units can be replaced during operation, ensuring consistent, redundant network availability.

- 750 watts power supply unit for improved failover of the LANCOM CS-8132F (F2B / B2F)
- Hot-swappable - can be applied during operation
- Input voltage: 100 VAC und 240 VAC
- Output voltage: +12 V @62.5 A, +5 Vsb @3 A
- Over current protection
- Over voltage protection
- Short circuit protection
- Operating temperature: 0°C to 40°C
- LANCOM SPSU-750-F2B for LANCOM CS-8132F-F2B
- LANCOM SPSU-750-B2F for LANCOM CS-8132F-B2F



LANCOM SPSU-750

Technical Information

Input voltage	100 - 240 VAC, 50 - 60 Hz
---------------	---------------------------

Output power	750 W
--------------	-------

Mechanical Information

Dimensions	263 mm (L) x 40 mm (H) x 50.5 mm (W)
------------	--------------------------------------

Weight	1200 g
--------	--------

Operating temperature	0° to 40°C
-----------------------	------------

Storage temperature	-40° to 70°C
---------------------	--------------

Support

Warranty extension	2 years
--------------------	---------

Further informations

Supported devices	→ LANCOM CS-8132F-F2B, article number: #61909 → LANCOM CS-8132F-B2F, article number: #61910
-------------------	--

Item number(s)

SPSU-750-F2B	61920
--------------	-------

SPSU-750-B2F	61921
--------------	-------