

Maximum freedom of design for guest Internet access

The LANCOM Public Spot Option provides reliable and secure Internet access for guests, visitors, partners or customers, all based on a common infrastructure. The guest network is at all times strictly and securely separated from the hotel's internal network. There is no need for any additional hardware components, which makes the LANCOM Public Spot Option the optimal solution for the provision of secure hotspots.

- → Secure separation of guest access from the internal network
- → Flexible configuration of authentication at the hotspot
- → Choice of models for online time and validity period of the guest access accounts
- → Voucher and portal layout can be customized to the individual design of the company
- → Connection to external servers or property management systems via XML, FIAS or RADIUS interfaces
- → Available in two variants: Public Spot Option and Public Spot XL option
- → Upgradeable with the LANCOM Public Spot PMS Accounting Plus option for connection to hotel billing systems
- → Simply upgrade your existing device and save on hardware components



Secure separation of guest access from the company LAN

The LANCOM hotspot solution operates on a single network infrastructure. The company and guest networks are securely separated from one another, and company data remains securely protected from unauthorized access. Integrity of this type yields enormous cost savings not only because it upgrades your existing hardware, but also because managing just one infrastructure reduces the administrative overhead.

A choice of login procedures

The LANCOM Public Spot solution offers a variety of options for guest authentication, including self-authentication by e-mail or SMS, printed voucher, confirmation of the terms and conditions, and others. This gives hotspot operators the choice of access provision that best suits their solution.

Flexible online time and validity

The LANCOM Public Spot Option offers flexibility in the design of the hotspot, particularly with regard to the available online time and the validity period. You can issue vouchers for a few hours, for entire days, or even for weeks. You can also specify a data volume limit after which access expires or the bandwidth is reduced. This gives you maximum flexibility and control.

Voucher layout and login portal in your corporate design

The LANCOM Public Spot Option offers a huge variety of configurations to facilitate an individual design. For example, the hotspot login page can be adapted to the corporate design of the hotspot operator. You can create your own banners, greeting messages, or even your own customized login pages. Strong branding for your hotspot.

Flexible interface structure

The LANCOM Public Spot Option offers a wide range of interfaces (API) for combination with external server solutions. XML, RADIUS or FIAS are used to connect it to external servers or property management systems (PMS). For example, the hotel can bill Internet charges directly to the room, or user authentication can be based on the guest's room number.

Easy upgrades

The LANCOM software options turn a simple network into a customized and cost-efficient solution that meets your individual needs. Simply install them on your existing hardware and you upgrade your network with the desired feature. The advantage: No additional hardware components are required. The costs and the administration overhead of the entire network are reduced. Genuine added value comes in terms of the system's future viability, because the options transform a network into a customized and scalable networking solution.




Technical details	
Supported devices	→ LANCOM 1800 series → LANCOM 1900-series → LANCOM 2100EF → LANCOM 17xx-series (as of LCOS 8.5) → LANCOM 88x-series → LANCOM IAP-5G → LANCOM access points
Number of supported users	→ LANCOM 1900 serie, LANCOM 2100EF 256 simultaneously configured user accounts → LANCOM 1800 series, LANCOM 17xx series, LANCOM 88x series 128 simultaneously configured user accounts → LANCOM IAP-5G, LANCOM access points (as of LCOS 8.5) 64 simultaneously configured user accounts
Login via web portal (Captive Portal)	Login to the hotspot after entry of username and password via a web portal (freely definable)
Self-service login to the hotspot (Smart Ticket)	Login credentials to the public spot network are sent to the user through SMS or e-mail. The e-mail is sent via SMTP. The sms is transmitted via the integrated 3G/4G modem, an e-mail-2-SMS gateway or a 3G/4G router in the network
Voucher print	With just a few mouseclicks tickets with login credentials for the hotspot can be generated and be printed with any office printer. The voucher can be individually designed.
Easy Public Spot login with one click	After accepting the terms of use, the user gets a WLAN guest access for a definable period
WISPr	Wireless Internet Service Provider roaming allows smart clients to connect to a Public Spot without the need of manual input of login credentials on a website.
Re-login	The Public Spot identifies known WLAN clients for an automatic authentication. After an initial authentication, the hotspot stores the relevant client information so that there is no need for an additional manual entering of login credentials - significantly increased comfort for regular guests.
MAC-based authentication	Users can be authenticated for access to the Public Spot via their MAC address
Walled Garden functionality	Enables a free access to selected websites, even without activation of the guest access (e.g. sponsoring, corporate or hotel websites)
Bandwidth management	The available bandwidth for Public Spot user groups (e.g. "gold", "silver", "bronze") can be individually configured: An ideal functionality for preferring "premium users" and for limiting the bandwidth of standard accounts
Support of volume- and time-based accounts	Validity of a hotspot access can be defined with regard to download volume limitation per user or to a limited time period
Redirection to advertisment websites	The Public Spot user can be redirected to advertisement websites of the provider at configurable time intervals
Dynamic VLAN allocation	Allocation of Public Spot users to individually configurable networks
Idle timeout-based disconnect	Connection will be disconnected after x minutes without Internet access



natic logout from the hotspot if the client is no longer seen in the WLAN, function only available for WLAN es s Public Spot users to login to one hotspot account with multiple devices fault the Public Spot records session-specific data for later billing on an internal RADIUS server. The forwarding external RADIUS server can be configured on a device with Public Spot, if required OM devices are equipped with an integrated SYSLOG. Alternatively, LANCOM devices can be connected to hal SYSLOG servers er to provide further authentication szenarios apart from login with username and password, the LANCOM espot solution can be connected to external servers via an XML interface
fault the Public Spot records session-specific data for later billing on an internal RADIUS server. The forwarding external RADIUS server can be configured on a device with Public Spot, if required OM devices are equipped with an integrated SYSLOG. Alternatively, LANCOM devices can be connected to nal SYSLOG servers er to provide further authentication szenarios apart from login with username and password, the LANCOM
external RADIUS server can be configured on a device with Public Spot, if required OM devices are equipped with an integrated SYSLOG. Alternatively, LANCOM devices can be connected to nal SYSLOG servers er to provide further authentication szenarios apart from login with username and password, the LANCOM
external RADIUS server can be configured on a device with Public Spot, if required OM devices are equipped with an integrated SYSLOG. Alternatively, LANCOM devices can be connected to nal SYSLOG servers er to provide further authentication szenarios apart from login with username and password, the LANCOM
nal SYSLOG serverser to provide further authentication szenarios apart from login with username and password, the LANCOM
es a direct communication between the LANCOM Public Spot and a Property Management System (PMS) supports the FIAS protocol as supported by Micros Fidelio. The interface can only be operated in combination he LANCOM Public Spot PMS Accounting Plus Option
ot users are provided an encrypted login to the LANCOM Public Spot in order to effectively prevent n-the-Middle attacks during login procedures. For this purpose, a signed certificate by a trusted certification rity must be imported into the device
NCOM access point/WLAN router with web browser (optional – MAC, Windows, Linux) work connection to Public Spot gateway nter with connection to the PC (optional)
al configuration incl. expert settings via proprietary LANCOM configuration tool or web interface
his wizard you can comfortably create vouchers with login credentials for the hotspot. The wizard can be d via a desktop shortcut.
rehensive manual for the configuration of LANCOM hotspots, including practical examples, available of-charge via www.lancom-systems.com
2





LANCOM Systems GmbH
A Rohde & Schwarz Company
Adenauerstr. 20/B2
52146 Wuerselen | Germany
info@lancom.de | www.lancom-systems.com

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 11/24