

## LANCOM DECT 510 IP

Professional DECT base station for LANCOM business-VoIP and All-IP enabled routers



The LANCOM DECT 510 IP base station is the ideal solution for small and medium-sized enterprises needing to integrate Gigaset DECT handsets. Once connected to the LANCOM router, the setup and configuration are automatic. The base station registers up to 6 DECT handsets and assigns them individual phone numbers. The LANCOM DECT 510 IP combines wireless telephony with exceptional HD voice quality.

- Easy integration into networks via LANCOM business VoIP routers and routers with an activated All-IP option
- Auto-provisioning of the base station via the LANCOM router
- Use of up to 6 DECT handsets
- 4 calls in parallel
- Telephony with highest voice quality
- Powered by Power over Ethernet or power supply unit
- Recommended DECT handsets: Gigaset SL800 PRO, SL750H PRO, S700H PRO, R700H Pro, S650H PRO, R650H PRO, R630H PRO, S510H PRO (other DECT handsets supporting the GAP standard can be used with reduced features)

# LANCOM DECT 510 IP

## **Easy network installation**

Fitting seamlessly into the overall solution, the LANCOM DECT 510 IP is the ideal DECT base station for LANCOM All-IP infrastructures. LANCOM business VoIP routers support the operation of ISDN, analog, and VoIP devices in parallel with DECT devices.

## **Auto-provisioning via the base station**

The LANCOM DECT 510 IP is an easy-to-use and time-saving solution for the setup and configuration of DECT handsets. The base station connects directly to the Ethernet port of the LANCOM router. The Voice Call Manager in the router recognizes the base station and enables the central management of the mobile handsets connected to it. DECT users can be conveniently registered with the base station via a configuration wizard.

## **Use up to 6 DECT handsets**

Once connected to a LANCOM router, the LANCOM DECT 510 IP supports up to 6 DECT handsets and assigns individual phone numbers to them.

## **4 call in parallel**

The LANCOM DECT 510 IP supports up to 4 calls in parallel, making it ideal for versatile communication in small and medium-sized enterprises.

## **Telephony with the highest voice quality**

If all of the participating networks and devices support HD voice, the Voice Call Manager in the LANCOM router delivers excellent quality of speech via the LANCOM DECT 510 IP. HD voice provides an improved audible presence for all of the participants who use DECT.

## **Powered by PoE or power supply unit**

By supporting Power over Ethernet (PoE), the LANCOM DECT 510 IP operates at a LANCOM PoE switch even at long distances away from the nearest power outlet. The base station can be freely positioned to supply the best possible DECT coverage. Alternatively, a power supply unit can be used.

# LANCOM DECT 510 IP

## Technical details

Supported devices	→ Business VoIP routers: LANCOM 1926VAG, LANCOM 1926VAG-4G, LANCOM 1926VAG-5G, LANCOM 1900EF-5G, LANCOM 1906VA, LANCOM 1906VA-4G, LANCOM 1900EF, LANCOM 1793VA, LANCOM 1793VAW, LANCOM 1793VA-4G(+), LANCOM 1783VA, LANCOM 1783VAW, LANCOM 1783VA-4G, LANCOM 1784VA, LANCOM IAP-1781VAW+, LANCOM (R)88x series, LANCOM ISG-1000, LANCOM ISG-4000 → Business VPN routers with All-IP enabled: LANCOM 1800 series, LANCOM 1790 series, LANCOM 1781 series, LANCOM 1640E, LANCOM 831A
-------------------	---

Recommended mobile handsets*	→ Gigaset SL800H Pro → Gigaset SL750H Pro → Gigaset S700H Pro → Gigaset R700H Pro → Gigaset S650H Pro → Gigaset R650H Pro → Gigaset R630H Pro → Gigaset S510H Pro
------------------------------	--

\*) Note Other DECT handsets supporting the GAP standard can be used with reduced features.

## VoIP

Number of local VoIP numbers / mobile handset	max.6
Number of simultaneous VoIP connections	Up to 4 voice channels in parallel
Codecs	G.711 , G.722, G.726, G.729, DTMF (Inband, RFC2833, SIP-INFO)
Media protocols	SIP, RTP
QoS	DiffServ marking of signaling (SIP) and media streams (RTP)

## Interfaces

LAN	10/100 Mbps, auto node hub, PoE compliant with IEEE 802.3af
DECT	→ Frequency range: 1.88 to 1.90 GHz (EMEA) → DECT EN 300-175 X → DECT wireless transmission up to 300m in the open and 50m in buildings

## Management and monitoring

LANconfig/web interface	Manual configuration with LANCOM's configuration tool or the web interface
LANmonitor	Monitoring application for Microsoft Windows for (remote) surveillance and logging of the status of LANCOM devices and connections.
Firmware update	Update via web interface (HTTP/S)

# LANCOM DECT 510 IP

## Hardware

Dimensions	105 mm x 46 mm x 132 mm (length x width x height)
Weight	0,26 lbs (120 g)
LED display	1 LED for status display
Power supply	6.5V 600mA, Power over Ethernet, compliant with IEEE 802.3af
Environment	For indoor use (IP20), maximum temperature range 5-45° C; humidity 0-80%; non-condensing
Mounting	Wall or tabletop mounting

## Declarations of conformity\*

CE	EN 55024:2010, EN 60950-1:2006/AC:2011, EN 300 328 V1.7.1, EN 301 893 V1.7.1
*) Note	You will find all declarations of conformity in the products section of our website at <a href="http://www.lancom-systems.com">www.lancom-systems.com</a>

## Scope of delivery

Power supply	External power adapter (230V), NEST 6.5 V / 0.6 A DC/S
--------------	--

## Support

Warranty	2 years support
----------	-----------------

## Item number(s)

LANCOM DECT 510 IP	61901
--------------------	-------