

## LANCOM Direct Attach Cable

Optimal interconnections between your LANCOM devices!



The LANCOM Direct Attach Cables enable fast and uncomplicated interconnections between LANCOM switches, gateways, and firewalls - a practical alternative to using individual SFP transceivers. Time and cost input are optimally balanced. All Direct Attach Cables are tested for compatibility with LANCOM products and guarantee highly reliable and fast connections.

- [LANCOM SFP-DAC10-1M /-3M](#)
- [LANCOM SFP-DAC25-1M /-3M](#)
- [LANCOM SFP-DAC40-1M /-3M](#)
- [LANCOM SFP-DD-DAC50-1M /-2.5M](#)

# LANCOM Direct Attach Cable

## LANCOM SFP-DAC10-1M / SFP-DAC10-3M

Direct attach cable for 10 Gbps networking of LANCOM switches



- Direct attach copper cable for usage in SFP+ ports
- Up to 10 Gbps link speed (1G / 10G)
- Full-duplex mode
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC25-1M / SFP-DAC25-3M**

Direct attach cable for 25 Gbps networking of LANCOM switches



- Direct attach copper cable for usage in SFP28 ports
- Up to 25 Gbps link speed
- Full-duplex mode
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## **LANCOM SFP-DAC40-1M / SFP-DAC40-3M**

Direct attach cable for 40 Gbps networking of LANCOM switches



- Direct attach copper cable for usage in QSFP+ ports
- Up to 40 Gbps link speed
- Full duplex operation
- Operating temperature 0–70 °C
- 1 m / 3 m cable length
- Swappable during system operation

# LANCOM Direct Attach Cable

## LANCOM SFP-DD-DAC50-1M / SFP-DD-DAC50-2.5M

Direct attach cable for 50 Gbps networking of LANCOM switches



- Stacking cable for creating a stack with LANCOM XS-6128QF
- Direct attach copper cable for usage in SFP-DD ports
- Up to 50 Gbps link speed
- Full duplex operation
- Operating temperature 0–70 °C
- 1 m / 2.5 m cable length
- Swappable during system operation

## LANCOM Direct Attach Cable

	<b>LANCOM SFP-DAC10-1M SFP-DAC10-3M</b>	<b>LANCOM SFP-DAC25-1M SFP-DAC25-3M</b>	<b>LANCOM SFP-DAC40-1M SFP-DAC40-3M</b>	<b>LANCOM SFP-DD-DAC50-1M SFP-DD-DAC50-2.5M</b>
<b>Item number</b>	<b>SFP-DAC10-1M</b> 61495 60194 (Bulk 8)	<b>SFP-DAC25-1M</b> 60180 60195 (Bulk 8)	<b>SFP-DAC40-1M</b> 60176 60196 (Bulk 8)	<b>SFP-DD-DAC50-1M</b> 60179 60197 (Bulk 8)
	<b>SFP-DAC10-3M</b> 60175	<b>SFP-DAC25-3M</b> 60181	<b>SFP-DAC40-3M</b> 60177	<b>SFP-DD-DAC50-2.5M</b> 60178
<b>Warranty</b>	2 years	2 years	2 years	2 years
<b>Note</b>	To use the LANCOM Direct Attach Cables in a LANCOM switch, at least LCOS SX 3.30 RU3 is required.			

LANCOM devices and other LANCOM accessories compatible to the LANCOM Direct Attach Cables can be found under [www.lancom-systems.com/products/software-accessories/accessories/lancom-direct-attach-cable#devices](http://www.lancom-systems.com/products/software-accessories/accessories/lancom-direct-attach-cable#devices)