

	UF-T60	UF-60 / UF-60 LTE	UF-160	UF-260	UF-360	UF-760
Category	Industrial	Desktop	Desktop	Desktop	Rack	Rack
Hardware properties						
Ports	5x GE copper, 2x SFP	4x GE copper	4x GE copper	4x GE copper, 1x SFP	4x GE copper, 2x SFP+	8x GE copper, 2x SFP+
Modem	-	LTE Advanced, (only UF-60 LTE)	-	-	-	-
Opt. extension modules	-	-	-	-	1G ETH, 1G SFP, 10G SFP+	1G ETH, 1G SFP, 10G SFP+, 40G QSFP+
Power supply & memory redundancy	-	-	-	-	-	✓
Max. system performance (individual measurements)³						
IDS / IPS throughput HTTPS (Mbps)	1,150	700	750	1,250	1,500	13,000
Firewall throughput TCP (Mbps)	3,700	3,500	3,550	4,450	11,600	49,830
VPN throughput IPSec (Mbps)	1,200	790	1,200	1,500	2,200	19,700
Concurrent sessions	1,000,000	1,000,000	1,000,000	2,000,000	4,000,000	16,700,000
Max. system performance (usage of all UTM functionalities)³						
UTM throughput HTTPS (Mbps)	200	150	170	340	420	3,400
Recommended number of VPN tunnels	25 – 50	5 – 25	25 – 50	100 – 200	200 – 1,000	1,000 – 5,000
Power						
Input voltage (V)	2x 12 – 36	100 – 240	100 – 240	100 – 240	100 – 240	100 – 240
Max. power consumption (W)	22.3	40	40	40	60	2x 300
Dimensions						
W x H x D (mm)	130 × 100 × 150	232 × 44 × 115 (without antennas for UF-60 LTE)	231 × 44 × 200	231 × 44 × 200	440 × 44 × 269	440 × 44 × 364

³ All throughput rates measured bidirectionally with 1,500 bytes packet size

You can find the service and support portfolio at: www.lancom-systems.com/service-support

For operation in a virtualized environment, the LANCOM vFirewall is also available with the same range of security functions as the hardware-based Unified Firewalls. Find out more at: www.lancom-systems.com/vfirewall